

2000XLS

Residential
Single / Dual

Swing Gate Operator



*For Swing Gates
UP TO 16 ft. long or
500 lbs. per leaf*



All Models Listed;
UL325 Compliant



Intertek

Supporters and Proud Members of



- Includes battery backup, receiver antenna, entry transmitter, AC transformer and all necessary mounting hardware for a post-mounted installation, 15" (38 cm) total offset
- Soft start/soft stop
- Easy transmitter programming with the touch of a button
- Controller with job button technology
- Low voltage system — no electrician or welding required
- 2-year warranty (residential applications only)

www.GateOpenerKing.com
Phone: 800.878.7829
Fax: 330.650.9004
sales@GateOpenerKing.com

ELECTRICAL

- 12 Volt DC / 7.0 amp hour, sealed, rechargeable battery (included). Battery charge is maintained by a 120V AC/60 Hz input and 14V AC, 28 VA, transformer
- Powered by a reliable 12 Volt DC motor
- Charging regulated circuit on control board. "Sleep draw" is 15 mA; "active draw" is 2 to 5 amps

MECHANICAL

- The control board can be programmed for pull-to-open or push-to-open
- Operating temp -5 F (-21C) to +160 F (71 C)
- Opening time: From 15 to 20 seconds
- Range of arm stroke: is up to 15" (33 cm)
- Operator length: with arm fully retracted is 33.75" (85.2 cm), mounting point to mounting point
- Operation, diagnostic and safety alarms
- Inherent obstruction sensing
- Soft start/soft stop—for long mechanical life expectancy
- Auto close adjustable 3–120 seconds delay

MODEL	TYPE	VOLTS	Max. Gate Length	Max Gate Weight	Gate Speed
PRO-SW2000 XLS	Single	12 V DC	16'	500 lbs.	15-20 sec
PRO-SW2002 XLS	Dual				



FEATURES:

- Solar Compatible
- Larger, higher powered, lower RPM motor
- Reduced gear motor noise
- Increased operating speed by 10%
- NEW rev-counter board with reed switch technology
- NEW controller with Jog Button technology used in GPX series
- Features GTO/PRO's true soft start and stop operation
- Extended Cycle Life - Enhanced motor design makes this opener ideal for today's single family homes or ranches
- Works on all types of gates;* chain link, tube, panel, ornamental, wood and vinyl
- Full systems capable, control board includes an adjustable obstruction sensing, gate sequencing and auto close settings
- U.L. rated for Class I. System certified to be in compliance with U.L. 325, 6th edition

CAUTIONS



- Automatic gates not for pedestrians
- Automatic gate operators designed for vehicular traffic only; operators are powerful and can cause serious injury or death; DIRECT ALL PEDESTRIAN TRAFFIC TO SEPARATE PEDESTRIAN GATE
- UL325 requires use of contact or non-contact anti-entrapment devices
- ASTM F2200 requires that all exposed rollers are covered

www.GateOpenerKing.com
Phone: 800.878.7829
Fax: 330.650.9004
sales@GateOpenerKing.com