

3000XLS

Swing Gate Operator

Residential
Single / Dual



*For Swing Gates
UP TO 16 ft. long and
650 lbs. per leaf*



All Models Listed;
UL325 Compliant



Intertek

Supporters and Proud Members of



- One button auto-memorization of digital transmitter code
- Includes battery backup, 318 MHz RF radio receiver, entry transmitter, AC transformer and all necessary mounting hardware for a post-mounted installation, 16" (40.6 cm) total offset
- Soft start/soft stop
- Solar capable
- Low voltage system — no electrician or welding required
- 2-year warranty (residential applications only)

www.GateOpenerKing.com
Phone: 800.878.7829
Fax: 330.650.9004
sales@GateOpenerKing.com

ELECTRICAL

- 12 Volt DC / 7.0 amp hour, sealed, rechargeable battery (included). Battery charge is maintained by a 120V AC/60 Hz input, 18V AC, 40 VA. output, transformer rectified to 14V DC through control board
- Powered by a reliable 12 Volt (120 Watt) DC motor, 16:1 planetary gear drive system.
- Charging regulated circuit on control board. "Sleep draw" is 15 mA; "active draw" is 3 to 7 amps.

MECHANICAL

- The control board can be programmed for pull-to-open or push-to-open
- Operating temp -5 F (-21C) to +160 F (71 C)
- Opening time: From 15 to 18 seconds.
- Range of arm stroke: is up to 16" (41 cm)
- Operator length: with arm fully retracted is 40.25" (102 cm), mounting point to mounting point
- Operation, diagnostic and safety alarms
- Inherent obstruction sensing
- Soft start/soft stop—for long mechanical life expectancy
- Auto close adjustable 3–120 seconds delay

CAUTIONS



- Automatic gates not for pedestrians
- Automatic gate operators designed for vehicular traffic only; operators are powerful and can cause serious injury or death; **DIRECT ALL PEDESTRIAN TRAFFIC TO SEPARATE PEDESTRIAN GATE**
- UL325 requires use of contact or non-contact anti-entrapment devices
- ASTM F2200 requires that all exposed rollers are covered

| MODEL | TYPE | VOLTS | Max. Gate Length | Max Gate Weight | Gate Speed |
|----------------|------------|---------|------------------|-----------------|------------|
| PRO-SW3000 XLS | Single | 12 V DC | 16' | 650 lbs. | 15-18 sec |
| PRO-SW3200 XLS | Second arm | | | | |

(solar charger optional)

DUAL GATES

- The PRO-SW3200XLS works as a second gate operator when combined with a PRO-SW-3000XLS. The PRO-SW3200XLS includes a 40ft power cable.



FEATURES:

- Solar Compatible
- Reintroduction of product
- Increased operating speed by 10%
- NEW rev-counter board with reed switch technology
- IMPROVED front mount and scraper seal design
- Features GTO/PRO's true soft start and stop operation
- Extended Cycle Life — Enhanced motor design makes this opener ideal for today's single family homes or ranches
- Works on all types of gates: chain link, tube, panel, ornamental, wood and vinyl
- Full systems capable, control board includes an adjustable obstruction sensing, gate sequencing and auto close settings
- U.L. rated for Class I. System certified to be in compliance with U.L. 325, 6th edition

www.GateOpenerKing.com
Phone: 800.878.7829
Fax: 330.650.9004
sales@GateOpenerKing.com