

GTO[®]/ACCESS SYSTEMS

PROFESSIONAL RESIDENTIAL

GPX-SL25
SLIDE GATE OPERATOR

For slide gates up to 24 ft. (7.3 m) long, 650 lbs. (294.8 kg) with a 20 ft. (6.1 m) opening.

Technology • Innovation • Quality
Since 1987



Available From:

www.GateOpenerKing.com
Phone: 800.878.7829
Fax: 330.650.9004
sales@GateOpenerKing.com



Technology • Innovation • Quality

Since 1987



Pad mount ready package includes battery backup, radio receiver, entry transmitter, AC transformer, and chain. Optional post mount and adjustable pad mount adapters are available.



GPX-SL25

RESIDENTIAL SERIES

For slide gates up to 24 ft. (7.3 m) long, 650 lbs. (294.8 kg) with a 20 ft. (6.1 m) opening.

The GPX-SL25 series will handle gates weighing up to 650 lbs. (294.8 kg) and 24 ft. (7.3 m) in length with a 20 ft. (6.1 m) opening, if all proper installation procedures have been followed.

Note: ball bearing rollers should be used on all gates.

FEATURES:

- ▶ Full systems capable “add on ready” heavy-duty control board includes adjustable obstruction sensing, gate sequencing and auto close settings (OFF and 3–120 seconds).
- ▶ Includes a built-in internal friction disc brake/lock.
- ▶ Optional post mount adapter available (not included).
- ▶ Chain disconnect for manual operation.
- ▶ Residential cycle rated to 100 cycles daily.

MECHANICAL:

- Operating temp -5 F (-21C) to +160 F (71 C).
- Opening time: 1 ft. (.31 m) per second maximum.
- #41 Chain 25 ft. with master link.
- Fully compatible accessory terminal block provides connections for safety loops, exit wands, intercoms, card readers, phone systems.
- Operation, diagnostic and safety alarms,
- Inherent obstruction sensing.

ELECTRICAL/POWER:

- 12 Volt DC / 7.0 amp hour, sealed, rechargeable battery (included). Battery charge is maintained by regulator on control board
- Powered by a reliable 12 Volt (1/4 HP) DC motor, case hardened steel gear reducer.
- “Sleep draw” is 40 mA; “active draw” is 2 to 9 amps.

DIMENSIONS:

Height: 12.5”
Depth: 12”
Width: 10.5”

SHIPPING WEIGHT:

50 lbs. (22.7 kg) Meets UPS shipping standards

WARRANTY:

2 Year (RESIDENTIAL application)

CLASS OF OPERATION:

Class I

SAFETY LISTINGS:

System Certified with UL325 5th Edition safety standards, ETL listed.

OPTIONS:

Solar Power: Second battery recommended (not included). 10-watt Solar Panel Charger (FM123)

Post Mount: requires the optional Post Mount adapter (R4983).

Adjustable Pad Mount Adapter: used to raise operator 6” to 10” above existing pad (R4984)

Dual Gates: For dual gate applications, add Dual Gate Kit (GPX-SL252).

SUGGESTED ACCESSORIES:

- Wireless Vehicle Sensor (R4500)
- Solar Panels (FM123)
- Transmitters (RB741/RB742)
- Digital Keypad (F310)

www.GateOpenerKing.com
Phone: 800.878.7829
Fax: 330.650.9004
sales@GateOpenerKing.com